

PBZ LLC 295 Wood Corner Rd. Lititz, PA 17543 717-738-7365 KickoutFlashing.com

This suggested specification has been prepared by PBZ LLC, manufacturers of Kickout Flashing by PBZ. Kickout Flashing by PBZ is a pre-cut and welded aluminum piece that is inserted as a rain diverter where a sloped roof line meets a vertical wall.

SECTION 07 71 40

ALUMINUM KICKOUT FLASHING

PART 1 GENERAL

1.1 SUMMARY

A. Provide kickout flashing (rain water diverter) at any connection of sloped roofing and vertical wall. Rain water to be diverted to gutter utilizing kickout flashing.

1.2 SUBMITTALS

- A. Product Data: Manufacturer's product data to be used, including:
 - 1. Preparation instructions and recommendations.
 - 2. Storage and handling requirements and recommendations.
 - Installation methods.

1.3 QUALITY ASSURANCE

A. Comply with governing codes and regulations. Material preference for product is aluminum (either uncoated or powder coated.)

1.4 DELIVERY, STORAGE AND HANDLING

- A. Deliver, store and handle materials and products in strict compliance with manufacturer's instructions and recommendations and industry standards. Protect from damage.
- B. Store products in manufacturer's labeled packaging until ready for installation.

PART 2 PRODUCTS

2.1 MATERIALS

- A. Manufacturer: Kickout Flashing by PBZ, 295 Wood Corner Rd., Lititz, PA 17543, 717-738-7365, KickoutFlashing.com
- B. Substitutions: As equal. Requests for substitutions will be considered in accordance with provisions of Section 01 60 00 Product Requirements.
- C. Material shall be 3003-H14 aluminum, with a thickness of 0.040," pre-formed and welded to approximate size of 6" x 6" x 10." Material shall not be field-formed.

- D. Material shall be uncoated aluminum or powder coated aluminum.
- E. Powder coated colors: black, bronze, sand, tan, white. Powder coating to meet AAMA 2604 specifications.

PART 3 EXECUTION

3.1 PREPARATION

A. Prepare substrates for attachment of kickout flashing.

3.2 INSTALLATION

A. Install in accordance with manufacturer's installation instructions and in proper relationship with adjacent construction.

3.3 CLEANING AND PROTECTION

- A. Protect installed products until completion of project.
- B. Clean product before Substantial Completion.

END OF SECTION